

Rotors Selection Guide

- F** Fixed Angle Rotors
- S** Swing-Out Rotors
- A** Adaptors available for smaller tubes
- R** Refrigerated Models

Mini

Model No.	Rotor Cat. No.	GRF-m2.0-6	GRF-m1.8-10
726-600	Max. Capacity	6 x 1.5/2.0 ml	16 x 0.2 ml
	Shape		
6,500/2,234/2,182	Max. RPM/RCF	6,500/2,234	6,500/2,182

Model No.	Rotor Cat. No.	AS-08061-02
726-1000	Max. Capacity	6 x 1.5/2.0 ml
	Shape	
10,000/5,000	Max. RPM/RCF	10,000/5,000

Model No.	Rotor Cat. No.	GRA-s0.2-32	GRF-m1.8-10	GRF-m2.0-12
726-1312	Max. Capacity	32 x 0.2 ml	10 x 1.8 ml cryotube	12 x 2.0 ml
	Shape			
13,500/12,300	Max. RPM/RCF	6,000/1,554 (1 row), 1,850/2 (row)	13,500/12,300	13,500/12,300

Micro

Model No.	Rotor Cat. No.	GRE-s0.2-32	GRE-m2.0-24	GRE-m2.0-36	GRE-m5.0-10
726-536	Max. Capacity	32 x 0.2 ml	24 x 2.0 ml	36 x 2.0 ml	10 x 5.0 ml
	Shape				
15,000/21,583	Max. RPM/RCF	15,000/14,187	15,000/21,206	15,000/21,206	15,000/21,583

Model No.	Rotor Cat. No.	GRE-M-s0.2-64	GRE-M-m2.0-18	GRE-M-m2.0-24	GRE-M-m2.0-30	GRE-M-m5.0-12	GRD-M-m2.0-8	GRD-M-m2.0-16
726-7304	Max. Capacity	64 x 0.2 ml	18 x 2.0 ml filter tube	24 x 2.0 ml	30 x 2.0 ml	12 x 5.0 ml	GLB-m2.0(8)	GLB-m2.0-4(16)
	Shape							
F 17,000, 27,237 S 13,000, 16,343	Max. RPM/RCF	12,500/10,237 (inner), 11,722 (outer)	15,000/18,891	17,000/27,237	14,000/21,124	15,000/22,967	13,000/16,343	13,000/15,682

Bench Top

Model No.	Rotor Cat. No.	GRF-G-s0.2-64	GRF-G-m2.0-30	GRA-G-15-24A	GRF-G-15-24	GRF-G-c15-12	GRF-G-50-8	GRF-G-c50-6	GRF-G-85-6	GRS-G-100-6	GRS-G-100-6
726-248	Bucket Cat. No.	-	-	GLB-15A-FA	-	-	-	-	-	GLB-b100-100	GLB-b50-100
726-2484	Max. Capacity	64 x 0.2 ml	30 x 2.0 ml	24 x 15 ml	24 x 15 ml	12 x 15 ml conical	8 x 50 ml	6 x 50 ml conical	6 x 85 ml	6 x 100 ml	6 x 50 ml
	Shape										
	Max. RPM/RCF	12,000/9,434 (inner), 10,803 (outer)	12,000/15,520	4,000/3,134	8,000/7,370 (inner), 8,872 (outer)	12,000/16,582	12,000/16,582	10,000/11,101	10,000/12,298	4,000/3,105	4,000/3,032

Rotor Cat. No.	GRS-G-100-6	GRS-G-100-6	GRS-G-100-6	GRS-G-100-6	GRS-G-100-6	GRS-G-100-6	GRS-G-100-6	GRS-G-100-6	GRS-G-100-6
Bucket Cat. No.	GLB-10-8-100	GLB-b50-100	GLB-bd15-100	GLB-250-250	GLB-c250-250	GLB-60-250	GLB-d20/10-250	GLB-r250-r250	GLP-mw-r250
Max. Capacity	6 x 8 x 10 ml vacutainer	6 x 2 x 15 ml	6 x 2 x 15 ml conical	4 x 250 ml	4 x 250 ml conical	4 x 60 ml	4 x 2 x (20 & 10 ml)	4 x 250 ml	4 x 4 MTPs
	Shape								
	Max. RPM/RCF	4,000/3,105	4,000/3,032	4,000/3,105	5,000/5,394	5,000/5,394	5,000/5,394	5,000/4,752 (20), 4,472 (10)	4,000/2,737

Model No.	Rotor Cat. No.	GRF-G-s0.2-64	GRF-G-m2.0-30	GRA-G-15-24A	GRF-G-15-24	GRF-G-c15-12	GRF-G-50-8	GRF-G-c50-6	GRF-G-85-6	GRF-G-250-6
726-580	Bucket Cat. No.	-	-	GLB-15A-FA	-	-	-	-	-	-
726-5804	Max. Capacity	64 x 0.2 ml	30 x 2.0 ml	24 x 15 ml	24 x 15 ml	12 x 15 ml conical	8 x 50 ml	6 x 50 ml conical	6 x 85 ml	6 x (250 & 15 ml)
	Shape									
	Max. RPM/RCF	12,000/9,434 (inner), 10,803 (outer)	15,000/24,249	4,000/3,134	8,000/7,370 (inner), 8,872 (outer)	12,000/16,582	12,000/16,582	10,000/11,101	10,000/12,298	8,000/9,588 (250), 9,395 (15)

Rotor Cat. No.	GRS-G-100-6	GRS-G-100-6	GRS-G-100-6	GRS-G-100-6	GRS-G-100-6	GRS-G-100-6	GRS-G-100-6	GRS-G-100-6	GRS-G-100-6
Bucket Cat. No.	GLB-b100-100	GLB-b50-100	GLB-10-8-100	GLB-bd15-100	GLB-250-250	GLB-c250-250	GLB-60-250	GLB-d20/10-250	GLB-r250-r250
Max. Capacity	6 x 100 ml	6 x 50 ml	6 x 8 x 10 ml vacutainer	6 x 2 x 15 ml	6 x 2 x 15 ml conical	4 x 250 ml	4 x 250 ml conical	4 x 60 ml	4 x 2 x (20 & 10 ml)
	Shape								
	Max. RPM/RCF	4,000/3,105	4,000/3,032	4,000/3,105	4,000/3,032	4,000/3,105	5,000/5,394	5,000/5,394	5,000/4,752 (20), 4,472 (10)

Rotor Cat. No.	GRS-G-r250-4	GRS-G-r250-4	GRS-G-r250-4	GRS-G-r250-4	GRS-G-r250-4	GRS-G-r250-4	GRS-G-r250-4	GRS-G-r250-4	GRS-G-r250-4
Bucket Cat. No.	GLB-r250-r250	GLP-mw-r250	GLB-r750-r750	GLB-500-r750	GLP-mw-r750	GLB-750-750	GLB-b750-750	GLB-500-750	GLP-mw-750
Max. Capacity	4 x 250 ml	4 x 4 MTPs	4 x 500 ml conical	4 x 500 ml	4 x 4 MTPs	4 x 750 ml	4 x 750 ml	4 x 500 ml	4 x 4 MTPs
	Shape								
	Max. RPM/RCF	4,000/3,134	4,000/2,737	3,600/2,898	3,600/3,159	3,600/2,485	4,000/3,667	4,000/3,900	4,000/3,068

Rotors Selection Guide

- F** Fixed Angle Rotors
- S** Swing-Out Rotors
- A** Adaptors available for smaller tubes
- R** Refrigerated Models

Bench Top

Model No.	Rotor Cat. No.	GRF-B-s0.2-64	GRF-B-m2.0-30	GRF-B-m2.0-48	GRF-B-m5.0-20	GRF-B-c15-12	GRF-B-15-12	GRF-B-15-24	GRF-B-c50-6	GRF-B-50-8	GRF-B-85-6
726-6964 R	Bucket Cat. No.	-	-	-	-	-	-	-	-	-	-
	Max. Capacity	64 x 0.2 ml	30 x 1.5/2.0 ml	48 x 1.5/2.0 ml	20 x 5.0 ml	12 x 15 ml conical	12 x 15 ml	24 x 15 ml	6 x 50 ml conical	8 x 50 ml	6 x 85 ml
	Shape										
	Max. RPM/RCF	12,000/9,434(inner), 10,803(outer)	16,000/27,590	15,000/21,206(inner), 24,602(outer)	13,500/22,209	15,000/25,910	15,000/25,155	8,000/7,370(inner), 8,872(outer)	13,000/18,592	15,000/25,910	12,000/17,709
	Rotor Cat. No.	GRF-B-250-6	GRS-G-100-6						GRS-B-r250-4		
	Bucket Cat. No.	-	GLB-b100-100	GLB-b50-100	GLB-dc50-100	GLB-bd15-100	GLB-bdc15-100	GLB-10-8-100	GLB-r250-r250	GLP-mw-r250	
	Max. Capacity	6 x 250 ml	6 x 100 ml	6 x 50 ml	6 x 2 x 50 ml conical	6 x 2 x 15 ml	6 x 2 x 15 ml conical	6 x 8 x 10 ml Vacutainer	4 x 250 ml	4 x 4 MTPs	
	Shape										
	Max. RPM/RCF	8,000/9,588	4,200/3,424	4,200/3,424	4,200/3,424	4,200/3,424	4,200/3,424	4,200/3,424	4,000/3,134	4,000/2,737	
	Rotor Cat. No.	GRS-B-250-4				GRS-B-r750-4			GRS-B-750-4		
	Bucket Cat. No.	GLB-250-250	GLB-c250-250	GLB-60-250	GLB-d20/10-250	GLB-r750-r750	GLB-500-r750	GLP-mw-r750	GLB-b750-750B	GLB-500-750B	GLP-mw-750B
	Max. Capacity	4 x 250 ml	4 x 250 ml conical	4 x 60 ml	4 x 2 x (20 & 10 ml)	4 x 500 ml conical	4 x 500 ml	4 x 4 MTPs	4 x 750 ml	4 x 500 ml	4 x 4 MTPs
	Shape										
	Max. RPM/RCF	5,000/5,394	5,000/5,394	5,000/5,394	5,000/4,752 (20), 4,472 (10)	3,600/2,898	3,600/3,159	3,600/2,485	4,600/4,850	4,600/5,157	4,000/3,900
	Rotor Cat. No.	GRS-B-1000-4									
	Bucket Cat. No.	GLB-h1000-1000	GLB-r1000-1000	GLB-b1000-1000							
	Max. Capacity	4 x 1000 ml	4 x 1000 ml	4 x 1000 ml							
	Shape										
	Max. RPM/RCF	3,700/3,092	3,700/3,084	3,700/3,337							

Bench Top

Model No.	Rotor Cat. No.	GRF-SR-m2.0-24	GRA-15-6A	GRA-S-15-16A	GRA-SR-15-24	GRF-SR-50-6	GRF-SR-c50-6	GRS-S-15-6	GRS-SR-15-6
726-406 Non-Ref.	Bucket Cat. No.	-	GLB-15A-FA	GLB-15A-FA	GLB-15A-FA	-	-	GLB-15-15	GLB-15-15
726-416 Non-Ref.	Max. Capacity	24 x 2.0 ml	6 x 15 ml	16 x 15 ml	24 x 15 ml	6 x 50 ml	6 x 50 ml conical	6 x 15 ml	6 x 15 ml
726-6244 Ref.	Shape								
	Max. RPM/RCF	6,000/3,393	4,000/2,075	4,000/2,700	4,000/2,469(inner), 2,773(outer)	6,000/3,824	6,000/3,960	4,000/2,826	4,400/3,420
	Rotor Cat. No.	GRS-S-50-4 (only for 416) / GRS-SR-50-4 (only for 6244)							
	Bucket Cat. No.	GLB-50-50	GLB-c50-50	GLB-15-50	GLB-c15-50	GLB-d15-50	GLB-dc15-50		
	Max. Capacity	4 x 50 ml	4 x 50 ml conical	4 x 15 ml	4 x 15 ml conical	4 x 2 x 15 ml	4 x 2 x 15 ml conical		
	Shape								
	Max. RPM/RCF	4,000/2,700 (416), 4,800/3,888 (6244)							
	Rotor Cat. No.	GRS-S-100-4 (only for 416) / GRS-SR-100-4 (only for 6244)				GRS-S-mw-2	GRS-SR-mw-2		
	Bucket Cat. No.	GLB-b100-100	GLB-b50-100	GLB-10-8-100	GLB-bd15-100	-	-		
	Max. Capacity	4 x 100 ml	4 x 50 ml	4 x 8 x 10 ml vacutainer	4 x 2 x 15 ml	4 x 2 x 15 ml conical	1 x 2 MTPs	1 x 2 MTPs	
	Shape								
	Max. RPM/RCF	4,000/2,774 (416), 4,200/3,059 (6244)	4,000/2,700 (416), 4,200/2,976 (6244)	4,000/2,774 (416), 4,200/3,059 (6244)	4,000/2,700 (416), 4,200/2,976 (6244)	4,000/2,774 (416), 4,200/3,059 (6244)	4,000/1,986	4,000/1,986	

Floor Stand

Model No.	Rotor Cat. No.	GRF-L-s0.2-64	GRF-L-m2.0-30	GRF-L-15-12	GRF-L-c15-12	GRF-L-50-6	GRF-L-c50-6	GRF-L-50-8	GRF-L-85-6	GRF-L-250-6	GRF-L-500-6
726-7364 Refrigerated	Bucket Cat. No.	-	-	-	-	-	-	-	-	-	-
	Max. Capacity	64 x 0.2 ml	30 x 2.0 ml	12 x 15 ml	12 x 15 ml conical	6 x 50 ml	6 x 50 ml conical	8 x 50 ml	6 x 85 ml	6 x (250 & 15 ml)	6 x 500 ml
	Shape										
	Max. RPM/RCF	12,000/9,434(inner), 10,803(outer)	17,000/31,147	17,000/32,310	15,000/25,910	17,000/32,310	15,000/24,753	15,000/25,910	15,000/25,029	10,000/14,981(250), 14,679(15)	8,000/11,305
	Rotor Cat. No.	GRS-L-r250-4									
	Bucket Cat. No.	GLB-r250-r250	GLP-mw-r250								
	Max. Capacity	4 x 250 ml	4 x 4 MTPs								
	Shape										
	Max. RPM/RCF	4,000/3,134	4,000/2,737								

Rotors Selection Guide

- F** Fixed Angle Rotors
S Swing-Out Rotors
A Adaptors available for smaller tubes
R Refrigerated Models

Model No.	Rotor Cat. No.	GRF-L-s0.2-64	GRF-L-m2.0-30	GRF-L-15-12	GRF-L-c15-12	GRF-L-50-6	GRF-L-c50-6	GRF-L-50-8	GRF-L-85-6	GRF-L-250-6	GRF-L-500-6
726-2364	Bucket Cat. No.	-	-	-	-	-	-	-	-	-	-
Refrigerated	Max. Capacity	64 x 0.2 ml	30 x 2.0 ml	12 x 15 ml	12 x 15 ml conical	6 x 50 ml	6 x 50 ml conical	8 x 50 ml	6 x 85 ml	6 x (250 & 15 ml)	6 x 500 ml
	Shape										
	Max. RPM/RCF	12,000/9,434(inner), 10,803(outer)	22,000/52,163	20,000/44,720	20,000/46,062	22,000/54,111	17,000/31,793	20,000/46,062	20,000/44,496	13,000/25,318(250), 24,808(15)	10,000/17,664
	Rotor Cat. No.	GRF-L-1000-4	GRF-L-1000-6	GRS-L-r250-4							
	Bucket Cat. No.	-	-	GLB-r250-r250	GLP-mw-r250						
		Max. Capacity	4 x 1,000 ml	6 x 1,000 ml	4 x 250 ml	4 x 4 MTPs					
		Shape									
		Max. RPM/RCF	8,000/12,071	7,000/10,825	4,000/3,134	4,000/2,737					

Model No.	Rotor Cat. No.	GRF-G-s0.2-64	GRF-G-m2.0-30	GRA-G-15-24A	GRF-G-15-24	GRF-G-c15-12	GRF-G-50-8	GRF-G-c50-6	GRF-G-85-6	GRS-G-100-6	
726-2361	Bucket Cat. No.	-	-	GLB-15A-FA	-	-	-	-	-	GLB-b100-100	GLB-b50-100
	Max. Capacity	64 x 0.2 ml	30 x 2.0 ml	24 x 15 ml	24 x 15 ml	12 x 15 ml conical	8 x 50 ml	6 x 50 ml conical	6 x 85 ml	6 x 100 ml	6 x 50 ml
	Shape										
	Max. RPM/RCF	12,000/9,434(inner), 10,803(outer)	12,000/15,520	4,000/3,134	8,000/7,370(inner), 8,872(outer)	12,000/16,582	12,000/16,582	10,000/11,101	10,000/12,298	4,000/3,105	4,000/3,032
	Rotor Cat. No.	GRS-G-100-6			GRS-G-250-4				GRS-G-r250-4		
	Bucket Cat. No.	GLB-10-8-100	GLB-bd15-100	GLB-bdc15-100	GLB-250-250	GLB-c250-250	GLB-60-250	GLB-d20/10-250	GLB-r250-r250	GLP-mw-r250	
		Max. Capacity	6 x 8 x 10 ml vacutainer	6 x 2 x 15 ml	6 x 2 x 15 ml conical	4 x 250 ml	4 x 250 ml conical	4 x 60 ml	4 x 2 x (20 & 10 ml)	4 x 250 ml	4 x 4 MTPs
		Shape									
		Max. RPM/RCF	4,000/3,105	4,000/3,032	4,000/3,105	5,000/5,394	5,000/5,394	5,000/5,394	5,000/4,752 (20), 4,472 (10)	4,000/3,134	4,000/2,737