

# Centrifuge Selection Guide

	MODEL	ROTOR	CONTAINERS																										
			MAX. RPM	RCF	8-tube POR STRIP	0.2-2.0 mL MICRO-TUBE	1.8 mL CRYO-TUBE	2.0 mL MICROFILTER-TUBE	5.0 mL MICRO-TUBE	3-5 mL TUBE & VACUTAINER	7 mL TUBE & VACUTAINER	10 mL TUBE & VACUTAINER	15 mL TUBE	15 mL conical TUBE	50 mL TUBE	50 mL conical TUBE	85 mL TUBE	100 mL TUBE	250 mL (C) TUBE	500 mL (C) BOTTLE	750 mL BOTTLE	1,000 mL BOTTLE	MICROPLATE	DEEPWELL PLATE	FILTER PLATE	10, 20 mL SYRINGE	60 mL SYRINGE	100 mL GLASS TUBE	
MINI	726-600	A	6,500 2,234		2	6	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	726-1000	A	10,000 5,000		-	6	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
	726-1312	A	13,500 12,300		4	12	10	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
MICRO	726-536	A	15,000 21,206		4	36	-	-	10	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
	726-7304	A	17,000 27,237		8	30	-	18	12	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
		S	13,000 16,343		-	16	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
BENCH TOP, LOW-SPEED	406	A	4,000 2,075		-	-	-	-	-	6	6	6	6	6	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
	726-416	A	4,000 2,700		-	-	-	-	-	16	16	16	16	16	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
		S	4,000 2,774		-	24	-	-	-	32	32	32	12	12	4	4	4	4	-	-	-	-	4	2	-	-	-	-	
	706-6244	A	6,000 3,960		-	24	-	-	-	24	24	24	24	24	6	6	-	-	-	-	-	-	-	-	-	-	-	-	
BENCH TOP, HIGH-SPEED	726-248	A	12,000 15,520		8	30	-	-	-	24	24	24	24	24	8	6	6	-	-	-	-	-	-	-	-	-	-	-	
		S	5,000 5,394		-	36	-	-	-	48	48	48	48	36	16	12	8	6	4	-	-	-	16	4	-	8	4	-	
	726-2484	A	12,000 16,582		8	30	-	-	-	24	24	24	24	24	8	6	6	-	-	-	-	-	-	-	-	-	-	-	
		S	5,000 5,394		-	36	-	-	-	48	48	48	48	36	16	12	8	6	4	-	-	-	16	4	-	8	4	-	
	726-580	A	15,000 24,249		8	30	-	-	-	24	24	24	24	24	8	6	6	-	-	-	-	-	-	-	-	-	-	-	
		S	5,000 5,394		-	36	-	-	-	120	80	80	80	64	32	20	8	6	4	4	4	4	16	4	-	8	4	-	
	726-5804	A	15,000 25,910		8	30	-	-	-	24	24	24	24	24	8	6	6	-	6(R)	-	-	-	-	-	-	-	-	-	
		S	5,000 5,394		-	36	-	-	-	120	80	80	80	64	32	20	8	6	4	4	4	4	16	4	-	8	4	-	
726-6964	A	16,000 27,590		8	48	-	-	20	48	48	48	48	48	8	6	6	-	6(R)	-	-	-	-	-	-	-	-	-		
	S	5,000 5,394		-	80	-	-	-	192	152	152	116	116	52	52	6	6	-	4	4	4	28	8	-	8	4	-		
FLOOR-STANDING, HIGH-SPEED	726-2361	A	12,000 16,582		8	30	-	-	-	24	24	24	24	24	8	6	6	-	-	-	-	-	-	-	-	-	-	-	
		S	5,000 5,394		-	36	-	-	-	48	48	48	48	36	16	12	8	6	4	-	-	-	16	4	-	8	4	-	
	726-7364	A	17,000 32,310		8	30	-	-	-	-	-	12	12	12	8	6	6	-	6(R)	6(R)	-	-	-	-	-	-	-	-	
		S	4,000 3,134		-	80	-	-	-	48	48	48	48	36	16	12	8	-	4(R)	-	-	-	16	4	-	-	-	-	
726-2364	A	22,000 54,111		8	30	-	-	-	-	-	12	12	12	8	6	6	-	6(R)	6(R)	-	6(R)	-	-	-	-	-	-		
	S	4,000 3,134		-	80	-	-	-	48	48	48	48	36	16	12	8	-	4(R)	-	-	-	16	4	-	-	-	-		